

Oil Free Vacuum Pump

Features

► Compact & care-free

Rocker oil-free pumps are compact in size, light in weight and oil-mist-free, making them the best pal in laboratory.

► Prote™ overflow protection

Equipped with Prote™ overflow protection to prevent liquid from being sucked into the pump.

► Air inlet protection

Filter cartridge at air inlet filters particles and moisture, which prevents pumps from damage.

► Vacuum regulation

Equipped with vacuum gauge and regulator for vacuum monitoring and adjustment.

► Overheat protection

All Rocker oil-free pumps are equipped with overheat protection device that shuts down when overheated and resumes once cooled down, making the pumps safer and long-lasting.

► International certification

CE certification
CSA certification (Rocker 300)
IP 30 protection (Rocker 300)
RoHS certification

► Two-Year Warranty

Applications

- Vacuum filtration
- Suspended solid test
- Microbiological test
- Air sampling

Ordering Information

167300-11(22)

Rocker 300, Vacuum Pump
AC110V, 60Hz (AC220V, 50Hz)

167330-00

Rocker 300DC, DC Power Vacuum
Pump (DC12V)



Specification

Model	Rocker 300		Rocker 300DC
PERFORMANCE DATA			
Max. vacuum	99 mbar abs.		99 mbar abs.
Max. flow rate	23 L/min @60Hz	20 L/min @50Hz	25 L/min
Hose barb	ID8		ID8
Noise level	50 dB		50 dB
Net weight	4.1 Kg		3.5 Kg
Dimension (LxWxH)	27 x 14 x 20 cm		27 x 12 x 17 cm
ELECTRICAL DATA			
Voltage	110V	220V	DC12V
Frequency	50 / 60Hz		-
Max. power	65W (1/8 HP)	60W (1/8 HP)	35W (1/8 HP)
Max. current	0.7A	0.3A	3.0A
Safety	Overheat Protection		Overheat Protection
OTHER DATA			
Equipped with	Vacuum regulator Overflow protection / Filter cartridge		Vacuum regulator Overflow protection / Filter cartridge